

Special Instructions for Ctek Installer 4.02.02

File name = Z4X00_4_02_02_04_installer_update.tar.gz

OEM/VAR Branded installers will include the OEM name in file name

Note: This notice applies only to the installer version of Ctek SkyRouter release 4.02.02. If you are updating using a binary flash file and the sam-ba utility, these instructions do not apply. The binary (flash) update will leave your machine at the 4.02.02 baseline release level and you will need to apply the four incremental patches using the built-in Flash Update client.

Important things to take away from this document:

- 1) This Installer will update SkyRouters from release level 4.01.07 through and including 4.02.02 to the 4.02.02.04 level. The trailing 04 indicates that this is 4.02.02 with 4 (four) patches applied. This installer has been tested with 4.01.05, 4.01.07, 4.02.00, and 4.02.02. If you are updating any other release level to 4.02.02.04 please contact Ctek first.
- 2) Installation using this process results in the unit being placed in a factory default condition
- 3) This installer can be applied from a LAN side Ethernet connection or over-the-air through a WAN connection. Special care must be taken when updating over the air. See below.
- 4) This installer will restore basic SkyRouter settings to the factory defaults. This means that the Wireless Interface is disabled, The LAN address is set to 192.168.1.10, DHCP is enabled, all DNS information is removed, and all branding information is removed.
The completed installation will leave existing licensed applications and customer developed applications in place. When updating from any release level prior to 4.02.02 Automation Control settings will be erased and will need to be reentered. If you are applying this to 4.02.02 the Automation settings will be preserved and operate normally after the machine is rebooted.

Installation Instructions

- 1) Install this release using the Ctek Option Installer process described in TechNote TN022.
- 2) After the restart, and before reconnecting to the SkyRouter either locally or over the air you **MUST** clear your browser's cache.

Information concerning installing over the air

- 3) You **MUST** remain connected to the unit's main administrative web screen while updating the unit using FTP.
- 4) Important – While navigating administrative screens after step 3 ONLY use the web browser's back arrow, NOT the back button on the screen.
- 5) Once the FTP Installer update completes use the previously connected admin screen to enable the wireless interface (Wireless Interfaces). Be sure to press update when completed.
- 6) Make any other changes (LAN, etc) required for your set up and then perform a restart. If you exit the browser before the restart, you can perform the restart using and SMS "BOOT" command. See TN009.